

American Environmental Associates, Inc.

5946 SOUTHLAND DRIVE • ERIE, PA 16509 PHONE (814) 866-7489 • FAX (814) 866-5693

UNDERGROUND STORAGE TANK FACILITY INTERIM SITE CHARACTERIZATION REPORT

Leo's 3 Car Wash
PADEP Facility I.D. #25-90615
2938 West 26th Street
Erie, Pennsylvania 16506

February 13, 2003


Prepared for:

Leo's 3 Car Wash 2938 West 26th Street Erie, Pennsylvania 16506 Attn: James Doleski

Prepared by:

American Environmental Associates, Inc. 5946 Southland Drive Erie, Pennsylvania

James Sturm, P.G. Sr. Hydrogeologist



PAUSTIF

TABLE OF CONTENTS

1.0 INTRODUCTION	1
2.0 SCOPE OF WORK	1-2
3.0 SITE GEOLOGY	2-3
4.0 GROUNDWATER MONITORING5.0 SUMMARY AND RECOMMENDATIONS	3 4-5
FIGURES	
Topographic Map	FIGURE 1
Geographic Location Map	FIGURE 2
Site Groundwater Contour Map	FIGURE 3
TABLES	
Analytical Results - Soil	TABLE 1
Groundwater / Separate Phase Hydrocarbon Gauging Data	TABLE 2
Groundwater Analytical Results	TABLE 3
APPENDICES	
	45551514.4
Soil Boring / Well Completion Logs	
Laboratory Analytical Report - Soil	
Laboratory Analytical Report - Groundwater	AFFENDIX C

INITIAL SITE CHARACTERIZATION REPORT

Leo's 3 Car Wash
PADEP Facility I.D. #25-90615
2938 West 26th Street
Erie, Pennsylvania 16506

1.0 INTRODUCTION

American Environmental Associates, Inc. (AEA) has been contracted by Leo's 3 Car Wash to provide environmental services pursuant to Underground Storage Tank (UST) corrective action and Land Recycling and Environmental Remediation Standards Act (Act 2) regulations at the subject site. The site is a retail gasoline filling station, oil change service and automated car wash located at 2938 West 26th Street, Millcreek Township, Erie County, Pennsylvania. The site location is illustrated on a USGS Topographic Map attached as Figure 1,the Geographic Location Map attached as Figure 2 and Figure 3 is the Site Groundwater Contour Map.

Corrective actions were initiated in response to a release that was discovered during construction of a new canopy on January 23, 2002. The release was eventually found to be associated with a loose swing joint in the regular unleaded line for the middle dispenser. A minor amount of contaminated soil was removed, approximately five tons, and then the new canopy footers were poured. The swing joint leak was repaired at this time. Clean soil conditions were never obtained, and over excavation was not performed at this time due to site constraints. A Notification of Contamination was submitted to the PADEP's Meadville Office on January 23, 2002.

On August 6, 2002, a Geoprobe investigation was conducted by AEA to assess the extent of subsurface soil contamination. Confirmatory soil analysis of samples from the unleaded gasoline UST system area exhibited concentrations in excess of Act 2 Statewide Health Standards (SHS). Corrective actions pursuant to 25 PA Code 245, administered by the Pennsylvania Department of Environmental Protection (PADEP), were implemented.

The following reports were prepared to document Site Characterization activities performed at the site:

 Initial Site Characterization Report, November 27, 2002; This report documents the installation and soil/groundwater sampling of monitoring wells MW#1 through MW#6. These wells were installed to delineate subsurface impacts.

The following report outlines the work that has been performed to delineate the extent of subsurface contamination at the subject site.

2.0 SCOPE OF WORK

On January 17, 2003, AEA mobilized to the site to install three additional four-inch monitoring wells (MW#'s 7, 8 & 9) on the subject site utilizing a hollow-stem auger drill rig. Split spoon sampling at 3 foot intervals was performed during soil boring advancement. The split spoon samplers were decontaminated between sampling intervals with a non-phosphatic soap (Alconox) solution and thoroughly rinsed with deionized water. The collected samples were utilized for lithologic description, headspace screening and subsequent laboratory analysis, as applicable.

Each sample was divided into two portions. One sample was placed in a sealable plastic bag to be used for field headspace screening. The other was set aside for potential laboratory analysis. The samples were field screened with a RAE Industries Mini-RAE 2000 photoionization detector (PID) to determine if Volatile Organic Compounds (VOC's) are present. Prior to the initiation of drilling, the instrument was calibrated using an appropriate span gas. The tip of the instrument was placed into the sample container and the highest reading was recorded. The results are summarized on the soil boring and well completion logs included as Appendix A. Also, refer to Site Geology, section 3.0, for more detailed information of the subsurface geology of the site. The sample from each boring exhibiting the highest PID response was submitted to Environmental Laboratory Services, Inc.(ELS), New Castle, PA for analysis.

The soil samples were analyzed for benzene, toluene, ethyl benzene, xylenes (BTEX), methyl-t-butyl ether (MTBE), cumene and naphthalene via EPA Method 5035/8260B. These analytes are indicator parameters for unleaded gasoline as referenced in PADEP's Technical Document: Closure Requirements for Underground Storage Tank Systems, April 1998. Soil analytical results are summarized in Table 1 and the lab sheets are included as Appendix B. The analytical results show that no new soil samples from MW#7, MW#8 or MW#9 exceed any of the PADEP's Statewide Health Standard's for Used Aquifers in soil. The analytical results indicate that the soil samples from previous drilling (MW#4, MW#5 & MW#6) exceed one or more of the PADEP's Statewide Health Standard's for Used Aquifers in soil.

The resultant soil borings were completed as 4-inch diameter PVC monitoring wells. The annular space was backfilled with well gravel and sealed with bentonite pellets. The remaining portion above the bentonite was sealed with concrete to prevent surface water infiltration. The wells were completed with eight inch diameter, bolt-down manholes and set in two feet square concrete pads. The monitoring wells were secured with watertight locking cap assemblies and keyed-alike padlocks. Soil boring and well completion logs are included as Appendix A.

A brief site reconnaissance of the nearby surroundings shows that residential and commercial dwellings rely on municipal water. Utilities running through the site exist no deeper than four feet below grade. With the shallowest static water level at the site being nearly 8 feet below grade, no potential human receptors exist at the site. Due to the detected constituents being associated with light petroleum products, no ecological screening is required.

3.0 SITE GEOLOGY

The regional geology underlying the project site is the Devonian aged Northeast Shale Formation. The Northeast Shale formation chiefly consists of variegated shale and thin-bedded sandstone. Sandstone generally yields small supplies of water. Site specific depth to bedrock is unknown since it was not encountered during the total drilling depth of twenty five feet. Unconsolidated materials, mainly silts, sands and clays, exist from grade to the total drilling depth of 25 feet. Refer to the Geologic Logs in Appendix A for further geologic information.

4.0 GROUNDWATER MONITORING

On January 22, 2003, all new site monitoring wells (MW#'s 1-9) were gauged utilizing a Solinst Model 122 electronic interface meter to measure the depth to water and to determine the potential presence of separate phase hydrocarbons (SPH's). Depth to groundwater was measured between 8.02 (MW#7) and 13.05 (MW#8) feet below ground surface. Free product or SPH's was encountered during the gauging of monitoring wells MW#3 & MW#4. Monitoring wells MW#3 & MW#4 were not sampled due to the presence of free product. Groundwater elevation data is presented in Table 2, and Figure 3 is a Site Groundwater Contour Map which has been generated from this data.

Each monitoring well was developed by purging at least five well volumes. The wells were then allowed to recover. Samples were collected utilizing dedicated disposable polyethylene bailers and placed in laboratory provided glassware containing an appropriate preservative. Samples were immediately placed in ice filled coolers and shipped to ELS in New Castle, PA under chain of custody protocol. The groundwater samples were analyzed for BTEX, MTBE, cumene, naphthalene, via U.S. EPA Methods 8260. These analytes are indicator parameters for unleaded gasoline as referenced in PADEP's Technical Document: Closure Requirements for Underground Storage Tank Systems, April 1998. The analytical results are summarized in Table 3 and the lab sheets are in Appendix C.

The analytical results indicate that monitoring wells MW#1, MW#2, MW#5, MW#6, MW#7 and MW#8 exceed Statewide Health Standards for Used Aquifers for one or more of the required parameters for unleaded gasoline in groundwater. Monitoring wells MW#3 & MW#4 were not sampled due to the presence of free product. The results are summarized in Table 3, and the groundwater sample lab sheets are attached in Appendix C.

5.0 SUMMARY AND RECOMMENDATIONS

American Environmental Associates, Inc. (AEA) has been contracted by Leo's 3 Car Wash to provide environmental services pursuant to Underground Storage Tank (UST) corrective action and Land Recycling and Environmental Remediation Standards Act (Act 2) regulations at the subject site. The site is a retail gasoline filling station, oil change service and automated car wash located at 2938 West 26th Street, Millcreek Township, Erie County, Pennsylvania. The site location is illustrated on a USGS Topographic Map attached as Figure 1,the Geographic Location Map attached as Figure 2 and Figure 3 is the Site Groundwater Contour Map.

Corrective actions were initiated in response to a release that was discovered during construction of a new canopy on January 23, 2002. The release was eventually found to be associated with a loose swing joint in the regular unleaded line for the middle dispenser. A minor amount of contaminated soil was removed, approximately five tons, and then the new canopy footers were poured. The swing joint leak was repaired at this time. Clean soil conditions were never obtained, and over excavation was not performed at this time due to site constraints. A Notification of Contamination was submitted to the PADEP's Meadville Office on January 23, 2002.

On August 6, 2002, a Geoprobe investigation was conducted by AEA to assess the extent of subsurface soil contamination. Confirmatory soil analysis of samples from the unleaded gasoline UST system area exhibited concentrations in excess of Act 2 Statewide Health Standards (SHS). Corrective actions pursuant to 25 PA Code 245, administered by the Pennsylvania Department of Environmental Protection (PADEP), were implemented.

Activities conducted during this reporting period include the installation and soil sampling of three additional monitoring wells (MW#7, MW#8 & MW#9), and the gauging and groundwater sampling of the site monitoring wells. The analytical results show that no new soil samples from MW#7, MW#8 or MW#9 exceed any of the PADEP's Statewide Health Standard's for Used Aquifers in soil. The analytical results indicate that the soil samples from previous drilling (MW#4, MW#5 & MW#6) exceed one or more of the PADEP's Statewide Health Standard's for Used Aquifers in soil. The analytical results indicate that monitoring wells MW#1, MW#2, MW#5, MW#6, MW#7 and MW#8 exceed Statewide Health Standards for Used Aquifers for one or more of the required parameters for unleaded gasoline in groundwater. Monitoring wells MW#3 & MW#4 were not sampled due to the presence of free product.

The Site Characterization work that is presently being performed is being compared to Pennsylvania Statewide Health Standards for soil and groundwater. Leo's 3 Car Wash is choosing this standard at this time.

Since the full extent of soil and groundwater contamination has not yet been determined, additional site characterization work will be performed in the near future.

FIGURE 1 Leo's 3 Car Wash

USGS 7.5 Minute Topographic Map 1:24,000 Scale




FIGURE 2 Leo's 3 Car Wash

Geographic Location Map

Figure 2. Geographic Location Map Leo's 3 Car Wash




Copyright © 1988-1997, Microsoft Corporation and/or its suppliers. All rights reserved. Please visit our web site at http://maps.expedia.com.

Page

FIGURE 3 Leo's 3 Car Wash

Site Groundwater Contour Map



TABLES

Table 1. Summary of Analytical Results- Soil Samples
Leo's 3 Car Wash
Erie, PA

Parameter	MW#1	MW#2	MW#3	MW#4	MW#5	MW#6	Z#MW	MW#8	6#MW	*SHS
Benzene	<0.1	0.26	0.10	7.26	0.59	1.33	<0.1	<0.1	<0.1	0.5
Toluene	<0.2	<0.2	1.23	61.8	0.31	95.0	<0.2	<0.2	<0.2	100
Ethyl benzene	06'0	3.39	3.45	17.6	0.38	14.9	<0.2	<0.2	<0.2	70
Xylenes	1.56	2.03	11.5	98.8	1.33	65.5	<0.2	<0.2	<0.2	1000
Cumene	<0.2	05.0	1.07	4.81	<0.2	0.55	<0.2	<0.2	<0.2	18
Naphthalene	0.29	0.82	1.71	3.42	<0.2	0.57	<0.2	<0.2	<0.2	10
MTBE	<0.2	<0.2	0.25	8.14	<0.2	<0.2	<0.2	<0.2	<0.2	2

Note: All results are in mg/kg or ppm.
Bolded numbers exceed allowable limits.
*SHS=Statewide Health Standard for Soil.

Table 2. Groundwater/ SPH Gauging Data Leo's 3 Car Wash Erie, PA

None None 9.45' 7.03' None None None None None None None None	Monitoring Well	Depth to SPH	Depth to Groundwater
None 9.45' 7.03' None None None None None None None	MW#1	None	11.35'
9.45' 7.03' None None None None	MW#2	None	10.25'
7.03' None None None None	MVV#3	9.45'	10.35'
None None None None	MW#4	7.03'	10.03'
None None	9#MW	None	8.50'
None	9#/\/W	None	11.13'
None	Z#MW	None	8.02'
	8#MW	None	13.05'
None	6#MW	None	12.42'

Note: SPH = Separate Phase Hydrocarbons

Table 3. Summary of Analytical Results- Monitoring Well Samples- 1/22/03 Leo's 3 Car Wash Erie, PA

Parameter	MW#1	MW#2	MW#3	MW#4	MW#5	MW#6	MW#7	MW#8	6#MW	**SHS
Benzene	0.051	0.153	NS	NS	9.93	2.51	0.002	0.014	<0.001	0.005
Toluene	<0.002	0.002			10.9	1.24	0.010	0.006	<0.002	1.0
Ethyl benzene	0.162	990.0			0.72	1.08	0.034	0.011	<0.002	0.70
Xylenes	0.508	0.094			4.59	3.71	0.128	0.035	0.002	10.0
Cumene	0.015	<0.002			<0.1	<0.1	0.004	<0.002	<0.002	0.025
Naphthalene	0.039	0.005			<0.1	0.30	0.032	0.009	<0.002	0.020
MTBE	0.077	0.075			37.4	0.68	<0.002	0.142	0.009	0.020

Note: All results are in mg/l or ppm.

Bolded numbers exceed allowable limits.

*NS=No Sample. This MW was not sampled due to the presence of Free Product.

**SHS=Statewide Health Standard for Groundwater.

APPENDIX A

Test Boring Logs

MW#1 Surface Elevation		'A	_
	r: 8_inches, inches,	From 0 To 25'	_
Total Depth:	25'		_
Depth of Ground	Water:		_
Date Measured:			

Drilling Method: HOLLOW-STEM AUGER Date Drilled: 10/29/02 Drilled By: CHATFIELD DRILLING Logged By: CHET ELEWSKI County: ERIE Township or Municipality: MILLCREEK TWP Project Name: LEO'S CARWASH

th	Lithelesia Missalatian	Strat.		nples	PID Meter	Comments	Dept (Ft.)
L)	Lithologic Discription	Symbol	No.	Rec/Att	Response		1, 0,
_		l					- α-
	oll Acquart					MANAPOLE COVER	
	6" ASPHALT 6"-3" SAND & BROWN					W/ LOCKING CAP CONCRETE COLLAR BENTONITE CLAY SEAL	
	SILTY SOIL	H. N. (2)				CONCRETE COLLAR	
	BROWN SILTY SAND &	4.		18"	36.2	BENTONTE CLAY SCAL	1
_	GRAVEL			10		5' OF SOLID WALL	5
<u> </u>						2" PVC PIPE	1
	BROWN GRAY SANDY SILT						1
							į
	DOWN ORAN CANDY SILT			16"	2379		
Λ.	BROWN GRAY SANDY SILT						10
0 —							
	BROWN GRAY SANDY SILT						
							1
	GRAY SILTY SAND			16"	65		1
5—	Alan Alel and		<u> </u>				15
_							
					•		-
			1		Ì	SAND PACK————————————————————————————————————	İ
			1	Ì	1		1 20
0	GRAY SILT & SHALE				İ	20° OF 0.010 SL01	20
			1		1	2" PAC SCREEN	
			}	1			
			ł		l		-
			1	1			25
25—						PVC END CAP	~
	1	1		1		PIC BID CA	İ
	· f	1	1		1	1	ŀ
		1	1	-	1		1
		1					30
50				1			"
				ļ			
	1					· F	
		1		1			
				1		1	3!
35			1				
		1	1				ł
		1					
	1					<u> </u>	
40-							4
40-	*** * * * * ***	:					
	I-152 6.004/008 F-88		1862981	91		dnoin BuileauiBu3 4723/201362.5	

Date Measured:_____

MW#2 Surface Elevation (MSL):N	/A	_
Casing Stickup: Borehole Diameter: 8 inches inches	s, From To	
Total Depth: 25'		_
Depth of Ground Water:		-

Drilling Method: HOLLOW-STEM AUGER

Date Drilled: 10/29/02

Drilled By: CHATFIELD DRILLING

Logged By: CHET ELEWSKI

County: ERIE

Township or Municipality: MILLCREEK TWP

Project Name: LEO'S CARWASH

		Strot.		nples	PID Meter	Comments
Lithologic D	iscription	Symbol	No.	Rec/Att	Response	CONTINUE
			_			
6" ASPHALT		457.5				WANGINE COVER W/ LOCKING CAP
8"-3' SAND &	DARK				1158	W/ LOCKING CAP
BROWN SILTY'S	OIL, HEAVY			1 1	,	CONCRETE COLLAR
PRODUCT OFOR		***************************************		1		
DARK BROWN	SANDY SILT,			14"	2871	BENTONITE CLAY SEAL
HEAVY PRODUC	LODOK	-		-		5' OF SOLID WALL
_						2° PVC PPE
DARK BROWN S	SANDY SILT					
		1:::::		16*	427	
BROWN DENSE	SILTY CLAY	(E==3		16	427	
		EEE 3				
BROWN DENSE	SILTY CLAY	£==3,				
BKOMM DEMOSE	OIL!! OEN	EEE3			l	
		•		100	10	↑ ※■ 科
BROWN GRAY !	SILIT SAND			10*	'0	
WEI		-		_		
				ļ		
						1
					1	SAND PACK————
				1		
				1		
GRAY SILT & W/SHALE LAYE	CLAY OC			1	1	20' OF 0.010 SLOT
MASIME PAIR	, na				i	
Į.		· · · · · · · · · · · · · · · · · ·			1	
					ł	
			<u> </u>	1		
				1		7
]			PVC END CAP-
-		1			1	1
				1	1	1
ł		1		1	1	
		1	1			
					1	
		1			\	1
1			l			
1			1		1	·
			1			
		}	1		1	
ł						
					1	
1				Ì		
					1	

		* -
	LEW	

Surface Elevation (MSL): N/A

Casing Stickup:
Borehole Diameter: 9_inches, From_0 To 24'9"
____inches, From_ To ___

Total Depth: 24'9"

Depth of Ground Water: ____

Date Measured: ____

Drilling Method: HOLLOW-STEM AUGER

Date Drilled: 10/30/02

Drilled By: CHATFIELD DRILLING

Logged By: JEREMY HOUK

County: ERIE

Township or Municipality: MILLCREEK TWP

Project Name: LEO'S CARWASH

Depth		Strat.	Sarr	ples	PID Meter	Comments	Depth
(Ft.)	Lithologic Discription	Symbol	No.	Rec/Att	Response	Commence	(Ft.)
		· ·					- o -
- 0 - -	2° ASPHALT DARK GRAY FINE SAND & ROCK FRAGMENTS	- 4			142	MANHOLE COMER W/ LOCKING CAP CONCRETE COLLAR BENTONTE CLAY SEAL " AROME SCREEN	
5-5	GRAY SAND & ROCK FRAGMENTS			8*	166		5 —
	GRAY SILT & SAND W/ROCK FRAGMENTS	A				4'-7" OF SOLIO WALL 2" PVC PIPE	
-10-	DENSE GRAY SILT			14"	22		10—
-	dense gray silt						1
-15-	0-7° dense gray silt 7-14° brown sand & rock Fragments, wet	. 4		14*	8		15-
	GRAY SHALE					SAND PACK 20° OF 0.010 SLOT 2° PVC SCREEN	20—
						PVC SND CAP	25—
-						PAC END CA-	_
-30					i.		30-
							-
_35							35
-							
40-		<u> </u>			<u> </u>		<u> </u>

11	14/	11	A
	w	22	-

Surface Elevation (MSL): N/A

Casing Stickup: Diameter: 9 inches, From 0 To 24'8"

—_____inches, From To _____

Total Depth: 24'8"

Depth of Ground Water: _____

Date Measured: _____

Drilling Method: HOLLOW-STEM AUGER

Date Drilled: 10/30/02

Drilled By: CHATFIELD DRILLING

Logged By: JEREMY HOUK

County: ERIE

Township or Municipality: MILLCREEK TWP

Project Name: LEO'S CARWASH

Depth		Strat.	Son	nples	PID Meter	Comments	Depth (Ft.)
(Ft.)	Lithologic Discription	Symbol	No.	Rec/Att	Response	50///	(Ft.)
							L- o -
0	4" ASPHALT FINE DARK GRAY SAND & ROCK FRAGMENTS	4			136	WANHOLE COVER W/ LOCKING CAP CONCRETE COLLAR BENTINMTE CLAY SEA	-
	BROWN & GRAY SAND, STRONG ODOR			15*	192	1 ABOVE SCREEN	5 —
5 - -	GREENISH GRAY SILT					4'-6" OF SOUD WALL 2" PMC PPPE	- -
- 40	BROWN & GRAY SILT W/ ROCK FRAGMENTS			10*	210		10-
 10 - -	GRAY SILT & SAND, WET						-
- 15	0-6° DENSE GRAY SILT 8-15" BROWN SAND 15-17" DENSE GRAY SILT			17*	120		15-
- - - - - 20	GRAY SILT &: SHALE					SAND PACK 20' OF 0.010 SLOT 2' PVC SCREEN	20-
 25 						PVC END CAP	
_ 30 							30-
- -							35-
35 							
_ _ 40_							40-

14	w	Ш	5
м	w	x	

Surface Elevation	(MSL):N/	Α	
Casing Stickup: Borehole Diamete	r: 9 inches,	From 0	To 19.5'
	inches,	From	. To
Total Depth:	19.5'		
Depth of Ground			
Date Measured:			

Drilling Method: HOLLOW-STEM AUGER
Date Drilled: 10/30/02
Drilled By: CHATFIELD DRILLING
Logged By: JEREMY HOUK
County: ERIE
Township or Municipality: MILLCREEK TWP
Project Name: LEO'S CARWASH

Chinese Description Symbol No. Res/Att Response Comments CFL	Depth		Strat.		ples	PID Meter	Comments	Depth
0 0 0 0 0 0 0 0 0 0	(Ft.)	Lithologic Discription					Comments	(Ft.)
BEOWN SAND & ROCK PROGRETS BROWN & SAND & ROCK PRAGMENTS BROWN & GRAY SAND AND COK PRAGMENTS BROWN & GRAY SAND AND COK PRAGMENTS DENSE GRAY SILT & ROCK PRAGMENTS DENSE GRAY SILT WITH COLOR PRAGMENTS OCITY DENSE GRAY SILT, WITH COCK PRAGMENTS GRAY SHALE 20 AUGER REFUSAL © 19.5' PIC DID CAP PIC DID CAP 25								
12 42 17 180K SOREN 12 12 12 13 14 15 15 15 10 15 15 15 15	├ ° -	BROWN SAND & ROCK	. 4				HANNICLE COVER W/ LOCKING CAP CONCRETE COLLAR	
BROWN & GRAY SAND AND ROCK FRAGMENTS DENSE GRAY SILT & ROCK 12" 24 10 DENSE GRAY SILT DENSE GRAY SILT OC-14" DOUSE PRAY SILT ROCK FRAGMENTS GRAY SHALE 20" 5.4 FAC DOUBLE FRAGMENTS GRAY SHALE 20 AUGER REFUSAL © 19.5" PVC DIO CAP 25	-	BROWN SAND & ROCK FRAGMENTS	2		12"	42	1' ABOVE SCREEN	5
DENSE GRAY SILT 0-14" DENSE GRAY SILT 20" 5.4	5-	BROWN & GRAY SAND AND ROCK FRAGMENTS					4'-5" OF SOUD WALL 2" PYC PIPE	
DENSE GRAY SILT	10-	DENSE GRAY SILT & ROCK FRAGMENTS			12"	24		10-
0-14* DOSE CRAY SHIT, WET 15* 19:51 19:52* BROWN SAND & 20* 5.4 -15	<u>-</u> 10-						SAND PACK	
GRAY SHALE 20 AUGER REFLISAL © 19.5' -25 -30 -35 -35	-15	0-14" DENSE GRAY SILT, WET 0 15"; 14-20" BROWN SAND & ROCK FRAGMENTS			20*	5.4		15-
20 AUGER REFUSAL © 19.5' -25 -30 -35 -35 -35 -35 -35 -35 -35 -35 -35 -35	-13-		· 	-			2° PAC SCREEN	
25	E	GRAY SHALE						
-30 -35 -35 -35	20	AUGER REFLISAL @ 19.5'	; ;				PVC END CAP	20-
-30 -35 -35 -35	_							
-30 35 35 35	- 25). -					25
-30 35 35 35	-							
-30 35 35 35	F							30-
	-30							
	E							-
40	35							35—
40	E							-
, , , , , , , , , , , , , , , , , , ,			<u> </u>					40
088-3 800/800 d 921-1 \$188299721 dno.19 8ui.188018u3 4723720 1382.15401-20159								

	ONO MELL LOG						
	ING WELL LOG	:					
MW#6	diana S	/*			Dailline	Method: HOLLOW-STEM AUGER	
Surface	Elevation (MSL): N	<u> </u>			_ Dote 1	Drilled: 10/30/02	
Casing S	Stickup:	. Casas	Λ	To 24'0'	_ Date :	By:_ CHATFIELD DRILLING	
Borehole	Diameter: 9 inches	From_	<u>v </u>	To Alle		d By: JEREMY HOUK	
	Inches	s, rrom_				y: ERIE	
Total De	pth: <u>24'9"</u> f Ground Water:				Towns	hip or Municipality: MILLCREEK T	NP
Depth of	Ground Water:	-			Projec	et Name: LEO'S CARWASH	
Date Me	asured:	i					
Depth		Strat.	San	nples	PID Meter	Comments	Depth
(Ft.)	Lithologic Discription	Symbol	No.	Rec/Att	Response	Oominicates	(Ft.)
							<u> </u>
<u> </u>	3" ASPHALT	1 1.				WANHOLE COVER W/ LOCKING CAP CONCRETE COLLAR BENTONTE CLAY SEA	-
-	BROWN SAND & ROCK					W/ LOCKING CAP CONCRETE COLLAR	-
	FRAGMENTS			 		W/ LOCKING CAP CONCRETE COLLAR BENTONTE CLAY SEAL	-
_	GRAY SAND & ROCK			24*	114	BENTONTE CLAY SEAL	
5—	FRAGMENTS	*********		 		4'-7' OF SOUD WALL	5 —
 -	GRAY-GREEN SILT			1		2" PVC PIPE	[]
-	GRAT-GREEN SILI						1 _
					114		-
	DENSE GRAY SILT			<u> </u>			10-
10							-
	GRAY SILT &: SAND	• • • • • • • • • •					-
	0-4" WET GRAY SAND	4 4 4 4 4 4 4 4 4					-
-	4-18" DENSE BROWN SILT			18"	10.4		15—
-15-							'5-
-	•						-
						SAND PACK————————————————————————————————————	-
							-
<u> </u>	GRAY SHALE & SILT					20' OF 0.010 SLOT	20-
		1				2° PVC SCREEN	1 -
-		1					
-							-
⊢ 25	<u> </u>						25-
<u> </u>			ı			PVC END CAP	-
_					1		_
_					i		-
							70
 30							30—
-				ļ			_
 	1			Ĭ	[-
		- [-
35				1			35-
			{				-
_				1			-
_			ļ			1	-
⊢		Į.					

MW#7

Surface Elevation (MSL): 100.94'

Casing Stickup: ______

Borehole Diameter: 8 inches, From 0 To 25'

_____inches, From To _____

Total Depth: _____25'

Depth of Ground Water: 8.02/92.92

Date Measured: 1/22/03

Drilling Method: HOLLOW-STEM AUGER

Date Drilled: 1/17/03

Drilled By: CHATFIELD DRILLING

Logged By: CHET ELEWSKI

County: ERIE

Township or Municipality: MILLCREEK TWP

Project Name: LEO'S CARWASH

Depth (Ft.)	Lithologic Discription	Strat. Symbol	San No.	nples Rec/Att	PID Meter Response	Comments	Depth (Ft.)
- o -	ASPHALT, CONCRETE, SAND & GRAVEL			_	_	MANHOLE COVER W/ LOCKING CAP CONCRETE COLLAR BENTONITE CLAY SEAL 1' AROME SCREEN	0
	BROWN GRAY SANDY SILTY CLAY			16"	20	BENTONITE CLAY SEAL 1' ABOVE SCREEN	5 —
1 -	BROWN GRAY SANDY SILTY CLAY		•			5' OF SOLD WALL 4" PVC PIPE	"
-10-	BROWN SILTY SAND & GRAVEL	4		16"	NMR		10—
⊢	BROWN SILTY SAND & GRAVEL						
_ —15—	GRAY SILT & SHALE CHIPS			_	-		15—
- - -	GRAY SILT & SHALE CHIPS					SAND PACK————————————————————————————————————	20—
						PVC END CAP	
_ 30 _							30
-							
35 							35—
-							-
-40							-40-

Surface Elevation (MSL): 100.33'
Casing Stickup:

Borehole Diameter: 8 inches, From 0 To 25' inches, From To _____

Total Depth: 25'

Depth of Ground Water: 13.05/87.28

Date Measured:____1/22/03

Drilling Method: HOLLOW—STEM AUGER

Date Drilled: 1/17/03

Drilled By: CHATFIELD DRILLING

Logged By: CHET ELEWSKI

County: ERIE

Township or Municipality: MILLCREEK TWP

Project Name: <u>LEO'S CARWASH</u>

Depth (Ft.)	Lithologic Discription	Strat. Symbol	San No.	nples Rec/Att	PID Meter Response	Comments	Depth (Ft.)
- o -	ASPHALT, CONCRETE, SAND & GRAVEL			_	-	MANHOLE COVER W/ LOCKING CAP CONCRETE COLLAR BENTONITE CLAY SEAL	0 -
_ _ 5—	BROWN GRAY SANDY SILTY CLAY			4"	15	1' ABOVE SCREEN [7]	5 —
- -	BROWN GRAY SANDY SILTY			-	-	5' OF SOLID WALL 4" PVC PIPE	5 —
_ 10 <i>_</i>	BROWN SILTY SAND & GRAVEL			16"	20		
_ io	BROWN SILTY SAND & GRAVEL			_			10—
_ —15—	GRAY SILT & SHALE CHIPS				-		15—
- - - - - - - - - - - - -	GRAY SILT & SHALE CHIPS					SAND PACK————————————————————————————————————	20—
- - -						PVC END CAP-	- - - -
30 							30—
- 35 - -							35— —
40							—40 —

Date Measured: 1/22/03

MW#9

Surface Elevation (MSL): 100.48'

Casing Stickup: _______

Borehole Diameter: 8 inches, From 0 To 25'

_____inches, From To _____

Total Depth: 25'

Depth of Ground Water: 12.42/88.06

County: ERIE

Township or Municipality: MILLCREEK TWP

Drilling Method: HOLLOW-STEM AUGER

Project Name: LEO'S CARWASH

Drilled By: CHATFIELD DRILLING
Logged By: CHET ELEWSKI

Date Drilled: 1/17/03

Depth (Ft.)	Lithologic Discription	Strat. Symbol	Sam No.	ples Rec/Att	PID Meter Response	Comments	Depth (Ft.)
- (,)		5)50.		1100/1100	Кооролоо		(,,
-0-	ASPHALT, CONCRETE, SAND & GRAVEL			-	-	MANHOLE COVER W/ LOCKING CAP CONCRETE COLLAR BENTONITE CLAY SEAL 1' AROME SCREEN	— 0 — - -
	BROWN SANDY SILTY CLAY & GRAVEL			14"	3	BENTONITE CLAY SEAL 1' ABOVE SCREEN	_
-	BROWN SANDY SILTY CLAY & GRAVEL			-	-	5' OF SOLID WALL 4" PVC PIPE	5 —
	BROWN SANDY SILTY CLAY & GRAVEL			12"	3		- 10—
	BROWN SANDY SILTY CLAY & GRAVEL			-	-		10 -
_ 15	GRAY SILT & SHALE			_	_		 15
	GRAY SILT & SHALE					SAND PACK————————————————————————————————————	20—
25 						PVC END CAP	25-
30 							30—
35 							35—
40							40 <u></u>

APPENDIX B

Laboratory Analytical Report- Soil

ANALYSIS REQUEST/ENVIRONMENTAL SERVICES CHAIN OF CUSTODY Method of Shipment: Personal Delivery Federal Express E.L.S. Pick Up Remarks U.P.S. Date Date Date Te l Meledras Received By: Received By Received By: Received By: Analysis Requested Time Time Time Time 63) ate Date Date Date SHE OBOH FIND Total # Containers Relinquished By: Relinquished By: Relinquished By: Other Water Matrix lio2 入 Phone (724) 552-5770 • Fax (724) 652-3814 1135 Butler Avenue New Castle, PA. 16101 Composite ປະເທ Colled Colled Date | Time Rush Environmental P.O. #: LEO'S 3CHRWMSH Services, Inc. (Rush TAT is subject to E.L.S. approval & surcharge) Normal Laboratory MELICHN ENV. Sample Identification Tumaround Time Requested: Rush Results Requested By. Project Name/#: PHONE Phone #: Project Manager. Billing Address: Fax #: 1110/28 Client: FAX

Time

Time

Time

Time

Environmental Laboratory Services, Inc. 5/98



(724) 652-5770

1135 Butler Avenue • New Castle, PA 16101

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

MW#7 (5'-8') Soil Sample

Sample Date: 01/17/03

Lab Sample #:

HW38706

EPA METHOD 5035/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/kg)	Detection Limit, (mg/kg)
Benzene, mg/kg	<0.1	0.1
Toluene, mg/kg	<0.2	0.2
Ethyl Benzene, mg/kg	<0.2	0.2
Xylenes, (Total, mg/kg	<0.2	0.2
Cumene, mg/kg	<0.2	0.2
Naphthalene, mg/kg	<0.2	0.2
MTBE, mg/kg	<0.2	0.2

Mark Swansiger

Lab Director



(724) 652-5770

1135 Butler Avenue • New Castle, PA 16101

FAX (724) 652-3814

REPORT DATE: 01/28/03

LABORATORY RESULTS

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

MW#8 (8'-10') Soil Sample

Sample Date:
Lab Sample #:

01/17/03 HW38707

EPA METHOD 5035/8260B

Result as Detection <u>Parameter</u> Received, (mg/kg) Limit, (mg/kg) Benzene, mg/kg <0.1 0.1 Toluene, mg/kg < 0.2 0.2 Ethyl Benzene, mg/kg < 0.2 0.2 Xylenes, (Total, mg/kg 0.2 < 0.2 Cumene, mg/kg < 0.2 0.2 Naphthalene, mg/kg < 0.2 0.2 MTBE, mg/kg < 0.2 0.2

Mark Swarze

Mark Swansiger Lab Director

(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name: Sample Date: 01/17/03

MW#9 (8'-10')

Lab Sample #:

HW38708

EPA METHOD 5035/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/kg)	Detection Limit, (mq/kq)
Benzene, mg/kg	<0.1	0.1
Toluene, mg/kg	<0.2	0.2
Ethyl Benzene, mg/kg	<0.2	0.2
<pre>Xylenes, (Total, mg/kg</pre>	<0.2	0.2
Cumene, mg/kg	<0.2	0.2
Naphthalene, mg/kg	<0.2	0.2
MTBE, mg/kg	<0.2	0.2

Mark Swansiger Lab Director

APPENDIX C

Laboratory Analytical Report- Groundwater

ANALYSIS REQUEST/ENVIRONMENTAL SERVICES CHAIN OF CUSTODY Method of Shipment: Personal Delivery Federal Express E.L.S. Pick Up Received By: Received By: Received By: Received By: **Analysis Requested** Time Time Time Time Date, Date Date 160 X Relinquished By: Relinquished By: Relinquished By: Other Water lio2 Phone (724) 552-5770 • Fax (724) 652-3814 1135 Buller Avenue New Castle, PA, 16101 Composite Colled Colled Date | Time Rush Environmental P.O. #. E 3 SCHKOMSH (Rush TAT is subject to E.L.S. approval & surcharge) Services, Inc. Normal Laboratory Furnaround Time Requested: Sample Identification Rush Results Requested By PHONE Phone #: Project Name/#: Project Manager: Billing Address: Fax #: D#01/4 CHM. 8×M 6 #0111 Mark C#/11/4 Client: FAX 4/23/2013 2:54:24 PM

Remarks

Time

<u>| (56/</u>

Time

Time

Date

Time



(724) 652-5770

FAX (724) 652-3814

1135 Butler Avenue • New Castle, PA 16101

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#1 Groundwater Sample

Sample Date: 01/22/03

Lab Sample #: HW38723

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	0.051	0.001
Toluene, mg/l	<0.002	0.002
Ethyl Benzene, mg/l	0.162	0.002
<pre>Xylenes, (Total, mg/l</pre>	0.508	0.002
Cumene, mg/l	0.015	0.002
Naphthalene, mg/l	0.039	0.002
MTBE, mg/l	0.077	0.002

Mark Swansiger/ Lab Director



(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#2 Groundwater Sample

Sample Date:

01/22/03

Lab Sample #: HW38724

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	0.153	0.001
Toluene, mg/l	0.002	0.002
Ethyl Benzene, mg/l	0.066	0.002
<pre>Xylenes, (Total, mg/l</pre>	0.094	0.002
Cumene, mg/l	<0.002	0.002
Naphthalene, mg/l	0.005	0.002
MTBE, mg/l	0.075	0.002





(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#5 Groundwater Sample

Sample Date: 01/22/03 Lab Sample #:

HW38725

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	9.93	0.05
Toluene, mg/l	10.9	0.1
Ethyl Benzene, mg/l	0.72	0.1
<pre>Xylenes, (Total, mg/l</pre>	4.59	0.1
Cumene, mg/l	<0.1	0.1
Naphthalene, mg/l	<0.1	0.1
MTBE, mg/l	37.4	1.0

Mark Swansiger

Lab Director

(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Monitoring Well MW#6 Groundwater Sample

Sample Date: Lab Sample #:

01/22/03 HW38726

> EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	2.51	0.05
Toluene, mg/l	1.24	0.1
Ethyl Benzene, mg/l	1.08	0.1
<pre>Xylenes, (Total, mg/l</pre>	3.71	0.1
Cumene, mg/l	<0.1	0.1
Naphthalene, mg/l	0.30	0.1
MTBE, mg/l	0.68	0.1

Mark Swarzuger

Mark Swansiger Lab Director

(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#7 Groundwater Sample

Sample Date: 01/22/03

Lab Sample #:

HW38727

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	0.002	0.001
Toluene, mg/l	0.010	0.002
Ethyl Benzene, mg/l	0.034	0.002
<pre>Xylenes, (Total, mg/l</pre>	0.128	0.002
Cumene, mg/l	0.004	0.002
Naphthalene, mg/l	0.032	0.002
MTBE, mg/l	<0.002	0.002





(724) 652-5770

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#8 Groundwater Sample

Sample Date:

01/22/03

HW38728 Lab Sample #:

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/l)	Detection Limit, (mg/l)
Benzene, mg/l	0.014	0.001
Toluene, mg/l	0.006	0.002
Ethyl Benzene, mg/l	0.011	0.002
<pre>Xylenes, (Total, mg/l</pre>	0.035	0.002
Cumene, mg/l	<0.002	0.002
Naphthalene, mg/l	0.009	0.002
MTBE, mg/l	0.142	0.002

Mark Swansiger (

Lab Director



(724) 652-5770

1135 Butler Avenue • New Castle, PA 16101

FAX (724) 652-3814

REPORT DATE: 01/28/03

Customer:

American Environmental

Generator:

Leo's 3 Car Wash

Sample Name:

Monitoring Well MW#9 Groundwater Sample

Sample Date: 01/22/03

Lab Sample #: HW38729

EPA METHOD 5030B/8260B LABORATORY RESULTS

Parameter	Result as Received, (mg/1)	Detection Limit, (mg/l)
Benzene, mg/l	<0.001	0.001
Toluene, mg/l	<0.002	0.002
Ethyl Benzene, mg/l	<0.002	0.002
<pre>Xylenes, (Total, mg/l</pre>	0.002	0.002
Cumene, mg/l	<0.002	0.002
Naphthalene, mg/l	<0.002	0.002
MTBE, mg/l	0.009	0.002

Mark Swansiger Lab Director